

LELIT Bianca

PL162T-120



TECHNICAL FEATURES

L58E group, paddle system with patented design, compatible with LELIT58 barista tools

Professional water/steam taps with spring closure

LCC with high-resolution OLED graphic display
Lack of water in the tank and "Reserve mode" graphic indicator

Possibility to activate Low Flow and Brew Temperature

Possibility to activate pre-infusion and stand-by times

Possibility of disabling the steam boiler

Partial and total doses counter

Coffee delivery timer

Temperature displayed in Celsius or Fahrenheit degrees

Double manometer for pump/steam pressure

L58E group manometer for coffee pressure

Water supply and direct discharge

Pump calibration via external adjustment screw

Polished stainless steel appliance body with cup warmer rack and drip tray with wire grate

Walnut wood knobs, lever, paddle and feet

I/O stainless steel back-lit switch

Anti-burn multidirectional steam and hot water wands

Mug friendly

Water tank placeable on the three sides of the machine

Coffee machine with L58E group and manual control of the water flow. The dual boiler ensures an excellent thermal stability. It is designed for the real homebarista that wants to get the best from each coffee.

Stainless steel steam boiler: 1.5 l

Stainless steel coffee boiler: 800 ml

Water tank: 2.5 l

Dimensions LxDxH: 29x58.5x39 cm

Weight: 27.2 kg

DELIVERED WITH

LELIT58 bottomless filterholder with walnut wooden handle

LELIT58 2-ways filterholder with walnut wooden handle and Coffee Slide spout

LELIT58 1 dose filter (9-11 g), IMS

LELIT58 2 doses filter (14-18 g), IMS

LELIT58 2 doses (18-21 g), IMS

LELIT58 blind filter, IMS

LELIT58 stainless steel tamper with aluminium handle

Spoon for coffee powder

Cup rack

70 l water softener filter

Small brush with nylon bristles

LELIT microfiber cloth

Optional 4-holes steam wand nozzle

First cleaning kit

PL162T-120

120 V 60 Hz | Plug Type B

LELIT Bianca

PL162T-120CB



TECHNICAL FEATURES

L58E group, paddle system with patented design, compatible with LELIT58 barista tools

Professional water/steam taps with spring closure

LCC with high-resolution OLED graphic display
Lack of water in the tank and "Reserve mode" graphic indicator

Possibility to activate Low Flow and Brew Temperature

Possibility to activate pre-infusion and stand-by times

Possibility of disabling the steam boiler

Partial and total doses counter

Coffee delivery timer

Temperature displayed in Celsius or Fahrenheit degrees

Double manometer for pump/steam pressure

L58E group manometer for coffee pressure

Water supply and direct discharge

Pump calibration via external adjustment screw

Black appliance body with cup warmer rack

New design drip tray with wire grate

Maple wood knobs, lever, paddle and feet

I/O stainless steel back-lit switch

Anti-burn multidirectional steam and hot water wands

Mug friendly

Water tank placeable on the three sides of the machine

Black coffee machine with L58E group and manual control of the water flow. The dual boiler ensures an excellent thermal stability. This machine is equipped with a new design drip tray. The final touch is given by its maple wood details.

AISI316L Stainless steel steam boiler: 1.5 l

AISI316L Stainless steel coffee boiler: 800 ml

Water tank: 2.5 l

Dimensions LxDxH: 29x58.5x39 cm

Weight: 26.5 kg

DELIVERED WITH

LELIT58 bottomless filterholder with maple wooden handle

LELIT58 2-ways filterholder with maple wooden handle and Coffee Slide spout

LELIT58 1 dose filter (9-11 g), IMS

LELIT58 2 doses filter (14-18 g), IMS

LELIT58 2 doses (18-21 g), IMS

LELIT58 blind filter, IMS

LELIT58 stainless steel tamper with maple wooden handle

Spoon for coffee powder

Cup rack

70 l water softener filter

Small brush with nylon bristles

LELIT microfiber cloth

Optional 4-holes steam wand nozzle

First cleaning kit

PL162T-120CB

120 V 60 Hz | Plug Type B

LELIT Bianca

PL162T-EUCW



TECHNICAL FEATURES

L58E group, paddle system with patented design, compatible with LELIT58 barista tools

Professional water/steam taps with spring closure

LCC with high-resolution OLED graphic display
Lack of water in the tank and "Reserve mode" graphic indicator

Possibility to activate Low Flow and Brew Temperature

Possibility to activate pre-infusion and stand-by times

Possibility of disabling the steam boiler

Partial and total doses counter

Coffee delivery timer

Temperature displayed in Celsius or Fahrenheit degrees

Double manometer for pump/steam pressure

L58E group manometer for coffee pressure

Water supply and direct discharge

Pump calibration via external adjustment screw

White appliance body with cup warmer rack

New design drip tray with wire grate

Maple wood knobs, lever, paddle and feet

I/O stainless steel back-lit switch

Anti-burn multidirectional steam and hot water wands

Mug friendly

Water tank placeable on the three sides of the machine

White coffee machine with L58E group and manual control of the water flow. The dual boiler ensures an excellent thermal stability. This machine is equipped with a new design drip tray. The final touch is given by its maple wood details.

Stainless steel steam boiler: 1.5 l

Stainless steel coffee boiler: 800 ml

Water tank: 2.5 l

Dimensions LxDxH: 29x58.5x39 cm

Weight: 26.5 kg

DELIVERED WITH

LELIT58 bottomless filterholder with maple wooden handle

LELIT58 2-ways filterholder with maple wooden handle and Coffee Slide spout

LELIT58 1 dose filter (9-11 g), IMS

LELIT58 2 doses filter (14-18 g), IMS

LELIT58 2 doses (18-21 g), IMS

LELIT58 blind filter, IMS

LELIT58 stainless steel tamper with maple wooden handle

Spoon for coffee powder

Cup rack

70 l water softener filter

Small brush with nylon bristles

LELIT microfiber cloth

Optional 4-holes steam wand nozzle

First cleaning kit

PL162T-120CW 120 V 60 Hz | Plug Type B